




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H01R 13/648</b>		<b>A1</b>	(11) International Publication Number: <b>WO 99/09616</b>
(21) International Application Number: <b>PCT/US98/17096</b>		(43) International Publication Date: <b>25 February 1999 (25.02.99)</b>	
(22) International Filing Date: <b>17 August 1998 (17.08.98)</b>		(81) Designated States: CN, JP, KR, SG, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(30) Priority Data: 60/056,596                      20 August 1997 (20.08.97)      US 60/076,277                      27 February 1998 (27.02.98)      US		<b>Published</b> <i>With international search report.</i>	
(71) Applicant (for all designated States except US): <b>BERG TECHNOLOGY, INC. [US/US]; One East First Street, Reno, NV 89501 (US).</b>			
(72) Inventors; and (75) Inventors/Applicants (for US only): <b>SHUEY, Joseph, B. [US/US]; 3425 Logan Street, Camp Hill, PA 17011 (US). STONER, Stuart, C. [US/US]; 559 Fishing Creek Road, Lewisberry, PA 17339 (US).</b>			
(74) Agents: <b>LONG, Daniel, J. et al.; 825 Old Trail Road, Etters, PA 17319 (US).</b>			

(54) Title: **HIGH SPEED MODULAR ELECTRICAL CONNECTOR AND RECEPTACLE FOR USE THEREIN**

## (57) Abstract

A receptacle (10) for an electrical connector comprising a housing having a first face (12) and a second face (16) and a plurality of signal conducting terminals (18) each extending from said first face to said second face and said housing having a plurality of longitudinal sides (24) interposed between said first face and said second face. A conductive shielding (32) is superimposed over at least some of said longitudinal sides. Interior conductive shielding is interposed between at least some of said signal conducting terminals.

**BEST AVAILABLE COPY**

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## HIGH SPEED MODULAR ELECTRICAL CONNECTOR AND RECEPTACLE FOR USE THEREIN

5

### Background of the Invention

1. **Field of the Invention:** The present invention relates to electrical connectors and more particularly to modular connectors for use in connecting a daughter printed wiring board to a mother printed wiring board.

10

2. **Brief Description of Prior Developments:** In the manufacture of computers and other various electronic assemblies, daughter boards are commonly connected to mother boards by means of a connector having a receptacle having a plastic housing and a first and second face wherein terminals are connected in one face to the daughter board and at the other to a header connected to the mother board. Various arrangements have been suggested to ground such connectors to the mother or daughter boards but such arrangements have tended to complicate the construction of the connector. A need, therefore, exists for simple and inexpensive means for grounding connectors between mother and daughter boards. There is also a need for such a connector which reduces crosstalk and increases band width.

15

20

### Summary of the Invention

The receptacle of the present invention comprises a housing having a first face and a second face and a plurality of signal conducting means.

25

Each of these terminals extends from said first face to said second face.

The housing has a plurality of longitudinal sides interposed between said first face and said second face, and there being a conductive shielding means superimposed over at least some of said longitudinal sides.

- 5 Interior conductive shielding means are interposed between at least some of said signal conductive means.

In the electrical connector of the present invention the above described receptacle is connected to a daughter board through a shielded header. The header has two end walls and a medial wall and is comprised  
10 of a conductive material, preferable a suitable metallic alloy. A plurality of apertures extend through the medial wall and retain signal pins which contact the terminals in the receptacle. There is a first and second face on the medial wall. The first face interfaces with the second face of the receptacle. The second face abuts the printed wiring board. On the  
15 second face there are a plurality of recesses into which conductive pins are press fitted to ground the connector.

### **Brief Description of the Drawings**

The invention is further described with reference to the accompanying drawings in which.

- 20 Fig. 1 is a cut-away perspective view of the receptacle of the present invention;

Fig. 2 is a perspective view of the exterior shielding used in the receptacle shown in Fig. 1;

Fig. 3 is a perspective view of the interior shielding used in the receptacle shown in Fig. 1;

Fig. 4 is a perspective view of the insulative housing used in the  
5 receptacle shown in Fig. 1;

Fig. 5 is a perspective view of the composite terminals and insulative frames used in the receptacle shown in Fig. 1;

Fig. 6 is a perspective view of the exterior shielding engaged to one of the interior shields;

10 Fig. 7 is a side elevational view of the receptacle shown in Fig. 1 which is cut-away to show terminal arrangement;

Fig. 8 is a front elevational view of the receptacle shown in Fig. 1;

Fig. 9 is a cross sectional view through 9 - 9 in Fig. 8;

Fig. 10 is a cross sectional view through 10 - 10 in Fig. 8;

15 Fig. 11 is a vertical cross sectional view through an insulative frame as is shown in Fig. 4;

Fig. 12 is a vertical cross sectional view of the receptacle shown in Fig. 1 engaged with a header.

Fig. 13 is a front perspective view of a second preferred embodiment  
20 of the receptacle of the present invention;

Fig. 14 is a rear perspective view of the receptacle shown in Fig. 13;

Fig. 15 is a rear elevational view of the receptacle shown in Fig. 13;

Fig. 16 is a schematic top cutaway view showing the receptacle engaging a printed circuit board;

Fig. 17A is a cross sectional view through 17 - 17 in Fig. 15;

5 Fig. 17B is a cross sectional view similar to Fig. 17A in which the receptacle is shown engaging a header;

Fig. 18 is a side elevational view of a shield used in a receptacle used in Fig. 13; and

10 Fig. 19 is a side elevational view of contacts used in the receptacle shown in Fig. 13.

Fig. 20 is a cutaway perspective view of a third preferred embodiment of the present invention;

Fig. 21 is a side elevational view of the receptacle shown in Fig. 20;

Fig. 22 is a front view of the receptacle shown in Fig. 20;

15 Fig. 23 is a bottom plan view of the receptacle shown in Fig. 20;

Fig. 24 is a rear end view of the receptacle shown in Fig. 20;

Fig. 25 is a side elevational view of an inner shield in the receptacle shown in Fig. 20;

Fig. 26 is a rear end view of the inner shield shown in Fig. 25;

20 Fig. 27 is a top plan view of the shield shown in Fig. 25;

Fig. 28 is a side elevational view of a composite insulative frame and conductive contact which is used in the receptacle shown in Fig. 20;

Fig. 29 is an end view of the insulative frame and contacts shown in Fig. 28;

Fig. 30 is a rear plan view of a fourth preferred embodiment of the receptacle of the present invention;

Fig. 31 is a bottom plan view of the receptacle shown in Fig. 30;

Fig. 32 is a cross sectional view through 32 - 32 in Fig. 30;

Fig. 33 is a bottom perspective view of the receptacle shown in Fig. 30;

Fig. 34 is a top perspective view of the receptacle shown in Fig. 30;

Fig. 35 is a rear plan view of the receptacle shown in Fig. 30 with the top shield removed;

Fig. 36 is a side elevational view of a header adapted to be connected to the receptacle shown in Fig. 30;

Fig. 37 is a top view of the header shown in Fig. 36;

Fig. 38 is a front plan view of the header shown in Fig. 36.

Fig. 39 is a side elevational view of a composite insulative frame and conductive contacts which may be used in the receptacle shown in Fig. 30;

Fig. 40 is an end view of the composite insulative frame and conductive contacts which is shown in Fig. 39; and

Fig. 41 is a top view of the composite insulative frame and conductive contacts shown in Fig. 40.

### Detailed Description of the Preferred Embodiments

Referring particularly to Figs. 1 - 2, the receptacle is shown generally at numeral 10. The receptacle has a first face 12 on a front insulative housing shown generally at numeral 14. The receptacle also has a second face 16 on its bottom side, and conductive signal terminals as at 18 extend from the first face to the second face. The first face has a plurality of openings as at 20 where, as is explained hereafter, pins from a header engage the signal terminals. As is conventional, the receptacle also includes ground pins as at 22. The receptacle also includes lateral longitudinal sides 24 and 26 and a top longitudinal side 28. In opposed relation to the first face there is an end 30. The longitudinal 24 and 26 and the end 30 are covered by a U-shaped shield 32. This shield is comprised of longitudinal sections 34 and 36 which are superimposed, respectively over longitudinal sides 24 and 26. In section 38 of the U-shaped shield 32 is superimposed over the end 30 of the receptacle 30. On longitudinal side 28 rearwardly of the insulative housing there is also a top shield (not shown).

Referring particularly to Figs. 1, 3 and 6, there are parallel longitudinal internal shielding walls 40, 42, 44, 46 and 48. Between these internal walls there are longitudinal spaces as at 50 (Fig. 3). Each of the internal walls also has a transverse section as at 52 and 53 (Fig. 3). Each of these transverse sections has a pair of vertical latches as at 54



and 56 on transverse section 52 and 58 and 60 on transverse section 53. These vertical latches engage horizontal eyelets as at 62 and 64 (Figs. 2 and 6). On the front top edge of the longitudinal section 34 of U-shaped shield 32 there is a spring latch 66. On the front top section of longitudinal section 36 of the U-shaped shield 32 there is also a spring latch 68. Similarly internal shielding wall 40 has a front spring latch 70, internal shielding wall 42 has a shielding latch 72, internal shielding wall 44 has a front spring latch 74, internal shielding wall 46 has a front shielding latch 76 and internal shielding wall 48 has a front spring latch 78.

Referring particularly to Fig. 4, there are side slots 80 and 82 in the insulative housing. These slots are engaged, respectively, by spring latches 68 and 70. Between these slots there are medial slots 84, 86, 88, 90 and 92 which are engaged, respectively, by spring latches 70, 72, 74, 76 and 78 on the internal shielding walls.

Referring particularly to Figs. 1 and 4 - 5, it will be seen that the terminals are enclosed within insulative frames 94, 96, 98, 100, 101 and 102. These frames have, respectively, frame latches 103, 104, 106, 108, 110 and 112. These frame latches engage, respectively, apertures 114, 116, 118, 120 and 122 in the insulative housing (Fig. 1).

Referring to Figs. 5 and 7 - 8 particularly, it will be seen that in addition to terminal 18, insulative frame 94 also holds signal terminal

124, 126, 128 and 130. Each of these terminals extends first upwardly and then horizontally. Each of these terminals has, respectively, at its horizontal terminal end a split pin engagement section 132, 134, 136, 138  
5 and 140. As is conventional, the receptacle also has a pair of code key holders 142 and 144 and press pins 146, 148 and 150.

Referring to Fig. 11, an insulative frame is shown as being vertically bisected. This bisected frame is centrally recessed and has a plurality of contact receiving structures 151a - 151h.

10 Referring to Fig. 12, the receptacle engages a header shown generally at numeral 152. The header has a pair of end walls 154 and 156 and a medial wall. There are apertures in the medial wall through which conductive pins as at 160 extend to engage the first face of the receptacle and be received in the split pin engagement sections of the  
15 terminals.

A second embodiment is shown in Figs. 13 - 20. Referring particularly to Fig. 13, the front face of the receptacle is shown generally at numeral 210 and a bottom face at 211. On this face there are conventional pin receiving apertures as at 212 for connection with the  
20 plug. The receptacle also includes, as is conventional, a press attachment peg 214 and location pegs 216 and 218. Also included are spacers 220 and 222 and polarization alignment keys 224 and 226.

Referring particularly to Figs. 14 - 15, the top face 228, rear face 230 and a side face 232 and 234 are shown in greater detail. From this figure it will be seen that there are slots as at 236 and 237 for receiving shields in the top face, bottom face and rear face which run parallel to the side faces. Between the shields there are elongated contact receiving slots as at 238 and 239. At vertical spaced intervals along the shield receiving slot there are also pairs of grooves 240 and 242.

Referring particularly to Figs. 16 - 20 signal contacts as at 244, 246, 248, 250 and 252 pass through each of the contact receiving slots in the receptacle. These contacts are connected at one end to the printed circuit board 254 (Fig. 16). (It will be understood that the contacts between individual sets of shields all extend rearwardly by the same overall length although in Fig. 16 engagement of the printed circuit board schematically shows several different rearward positions to illustrate various positions on the board which may be engaged by the contacts.) At their other end they have a V-shaped structure as at 256 to engage pins at the pin receiving apertures. Referring particularly to Figs. 17A - 17B and 19 the shields have ground pins as at 258, 260 and 262 that pass through the bottom face of the receptacle to be grounded to the PCB. The shield also has a lower resilient ground 264 which extends downwardly through a lower slot in the receptacle then rearwardly to be grounded to a

shrouded header 265 (Fig. 17B). Similarly the shield has an upper resilient ground structure 266 which passes through one of the slots in the upper face of the receptacle to be grounded to a header (not shown).

5 A header which would be suitable for engagement with these resilient ground projections would, for example, be either one shown in International Patent Application No. WO96/31922, published October 10, 1996 and assigned to the assignee of this application.

A third embodiment is shown in Figs. 20 - 29. The front face of  
10 the receptacle is shown generally at numeral 410 and a bottom face at 411. On this face there are conventional pin receiving apertures as at 412 for connection with the plug. The receptacle also includes, as is conventional, a press attachment peg 414 and location pegs 416 and 418.

The top face 428, rear face 430 and a side face 432 and 434 are  
15 shown in greater detail. As in the above cited related applications, there are slots for receiving shields in the top face, bottom face and rear face which run parallel to the side faces. Between the shields there are elongated contact receiving slots. At vertical spaced intervals along the shield receiving slot there are also pairs of grooves.

20 Referring particularly to Figs. 25 - 27, the shields have ground pins as at 458 that pass through the bottom face of the receptacle to be grounded to the PCB. The shield also has a lower resilient ground 458 which extends downwardly through a lower slot in the receptacle then

rearwardly to be grounded to a shrouded header. The shield has a rearward section 461 which extends perpendicularly from the main section 463. This rearward section 461 has another lower resilient ground 465. Similarly the shield has an upper resilient ground structure 466 which passes through one of the slots in the upper face of the receptacle to be grounded to a header (not shown). A header which would be suitable for engagement with these resilient ground projections would (for example) either one shown in International Patent Application No. WO96/31922, published October 10, 1996 and assigned to the assignee of this application.

Referring particularly to Fig. 29 - 30, a frame is shown in which the contacts as at contact 467 are held by an insulative member 469. The contacts are integral with the insulative member 469 and at one end they have a terminal as at terminal 471 and at the other end they have a V-shaped structure as at structure 456 to engage pins at the pin receiving aperture. The insulative member 469 also includes mounting recesses as at recess 473 which serve as a ground connection between the contact and the exterior shield.

Referring to Figs. 30 - 35, a fourth preferred embodiment of the receptacle shown generally at numeral 810. This receptacle has a first face 812 at its front of housing 814 and a second face 816 on its bottom side. A plurality of conductive signal terminals as at terminal 818

extends from the first face 812 to the second face 818. The first face 812 has a plurality of openings in rows 820a, 820b, 820c, 820d and 820e. In these openings pins from a header, described hereafter, engage signal  
5 terminals. The receptacle also includes lateral longitudinal sides 824 and 826 and a top longitudinal side 828. The receptacle also includes an end 830, and an angular external shield 832 is superimposed over the end 830 and the top longitudinal side 828. The longitudinal side 824 is made up of a metallic wall 834. Referring particularly to Fig. 37, it will be seen  
10 that there are a plurality of internal shielding walls 838, 840, 842, 844, 846 and 848. Adjacent each of these internal shielding walls there is a longitudinal air space 850a, 850b, 850c, 850d, and 850e. Each conductive shield has an upper contact latch 852a, 852b, 852c, 852d, 852e and 852f. Similarly these conductive shields also have a lower latch  
15 854a, 854b, 854c, 854d, 854e and 854f (Fig. 36). In the external shield 832 there are also top slots 858a - 858f to accommodate the spring latches 852a - 852f. There are also edge slots 858a - 858c to facilitate bending of the external shield 832 to its angular position. The shield also include bottom slots 860a - 860f to accommodate the lower spring contact  
20 latches.

Referring to Fig. 35, interposed between the conductive shields there are insulative frames 894, 896, 898, 900, 902 and 904. These

frames serve to retain the contacts in a way similar to the embodiments described before. For example, in addition to terminal 818 insulative frame 894 holds signal terminals 924, 926, 928 and 930. Each of these terminals extends first upwardly then horizontally. Each of these terminals has respectively at its horizontal end a split pin engagement section 932, 934, 936, 938 and 940. A receptacle also includes a lower conductive plate 941 which has perpendicular extensions 942 and 944. The lower plate 941 has horizontal extensions 946 and 947 which engage mating header pins through respective recesses 946 and 947 extending from the housing. The housing also includes longitudinal partitions 949a - 949e, interposed between these partitions there are contacts 950a - 950e.

Referring to Figs. 36 - 38, a header which is adapted to engage receptacle 810 is shown generally at 952. This header includes end walls 954 and 956 and a medial wall 958. The header also includes rows of signal pins 960a - 960e. There is also a shortened row of ground pins 962. In opposed relation to the pins 960a - 960e there are terminals 972a - 972e, and in opposed relation to pins 962 there are terminals 974. In wall 954 there are also ground contacts 976 and 978.

Referring to Figs. 39 - 41, a preferred insulative frame includes for use in the receptacle shown in Fig. 30 includes contacts as at contact 967 held by an insulative member 969. The contacts are integral with the

insulative member 969 and at one end they have a terminal and at the other end they have a V-shaped structure as at structure 1056 to engage pins at the pin receiving aperture. The insulative member 969 also  
5 includes mounting recesses as at recesses 975 and 977 which serve as ground connections between the contacts and the interior shell.

It will be appreciated that there has been described a simple and inexpensive receptacle which provides for effective shielding and grounding between mother and daughter boards, as well as signal  
10 carrying conductors.

While the present invention has been described in connection with the preferred embodiments of the various figures, it is to be understood that other similar embodiments may be used or modifications and additions may be made to the described embodiment for performing the  
15 same function of the present invention without deviating therefrom. Therefore, the present invention should not be limited to any single embodiment, but rather construed in breadth and scope in accordance with the recitation of the appended claims.



**Claims****WHAT IS CLAIMED IS:**

1. A receptacle for an electrical connector comprising a housing having  
5 a first face and a second face and a plurality of signal conducting means  
each extending from said first face to said second face and said housing  
having a plurality of longitudinal sides interposed between said first face  
and said second face and there being a conductive shielding means  
superimposed over at least some of said longitudinal sides and there  
10 being interior conductive shielding means interposed between at least  
some of said signal conductive means.
2. The receptacle of claim 1 wherein internal shielding means  
comprises a plurality of parallel longitudinal walls to form a plurality of  
15 longitudinal spaces between said longitudinal walls and one of said  
conductive means is positioned in each of said longitudinal spaces.
3. The receptacle of claim 2 wherein the conductive signal means are  
retained in a plurality of insulative frames.  
20
4. The receptacle of claim 3 wherein the conductive signal means are  
flattened to be interposed between adjacent internal conductive shielding  
means.
- 25 5. The receptacle of claim 4 wherein latching means are provided to fix  
each of said insulative frames to the housing.


6. The receptacle of claim 5 wherein each of the internal longitudinal walls has a transverse extension and each of said transverse extensions has a means for engaging said extensions to said exterior shielding.
- 5
7. The receptacle of claim 6 wherein the transverse extension has a vertical latch which engages a horizontal eyelet projecting from the exterior shielding means.
- 10 8. The receptacle of claim 7 wherein each of the internal longitudinal shielding means has a means for connecting said shielding means to the header.
9. The receptacle of claim 8 wherein the means for connecting said  
15 shielding means to the header are spring connecting means.
10. The receptacle of claim 1 wherein grounding means are provided.
11. An electrical connector comprising in combination a receptacle  
20 comprising a receptacle for an electrical connector comprising a housing having a first face and a second face and a plurality of signal conducting means each extending from said first face to said second face and said housing having a plurality of longitudinal sides interposed between said first face and said second face and there being a conductive shieldin  
25 means superimposed over at least some of said longitudinal sides and there being interior conductive shielding means interposed between at

least some of said signal conductive means and a housing having a first face and a second face and a plurality of conductive means each extending from said first face to said second face and a header having a conductive housing comprising generally parallel end walls with opposed inner faces and a medial wall is interposed between said opposed parallel end walls, said medial wall having a first face and a second face wherein said first face of the medial wall is adjacent to the second face of the receptacle element and a plurality of passages extend between the first and second faces of the medial walls and a plurality of conductive signal pins pass through at least some of said passages and a separate grounding means is attached to the conductive housing of the header.

12. An electrical connector comprising in combination a receptacle comprising a receptacle for an electrical connector comprising a housing having a first face adjacent a bottom side and a second face and a plurality of signal conducting means each extending from said first face to said second face and said housing having a plurality of longitudinal sides interposed between said first face and said second face and there being a conductive shielding means superimposed over at least some of said longitudinal sides and there being interior conductive shielding means interposed between at least some of said signal conductive means and a housing having a first face and a second face and a plurality of conductive means each extending from said first face to said second face and a header having a conductive housing comprising generally parallel end walls with opposed inner faces and a medial wall is interposed between said opposed parallel end walls, said medial wall having a first face and a

second face wherein said first face of the medial wall is adjacent to the second face of the receptacle element and a plurality of passages extend between the first and second faces of the medial walls and a plurality of conductive signal pins pass through at least some of said passages and a  
5 separate grounding. means is attached to the conductive housing of the header and on the bottom side there are ground contacts

1/30



2/30




FIG. 2

3/30




FIG. 3

4/30




FIG. 4



5/30




FIG. 5

6/30




FIG. 6









FIG. 12





9/30




FIG. 13

10/30




FIG. 14

11/30







FIG. 15








13/30



14/30



15/30



16/30




FIG. 22

17/30




FIG. 21




FIG. 23

18/30









FIG. 24



20/30





21/30




FIG. 30

22/30






FIG. 31

23/30



24/30



25/30




FIG. 34

26/30




FIG. 35

27/30




FIG. 36

28/30





FIG. 37



29/30

*FIG. 38*

30/30




FIG. 41




FIG. 39




FIG. 40

## INTERNATIONAL SEARCH REPORT

 International application No.  
 PCT/US98/17096

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :H01R 13/648

US CL :439/608

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 439/608, 607, 79, 108, 701

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
noneElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
none

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,718,606 A (RIGBY et al) 17 February 1998 (17.02.98), see the entire document.	1-12
A	US 4,973,260 A (MADORE et al) 27 November 1990 (27.11.90), see the entire document.	1-12
A	US 5,672,064 A (PROVENCHER et al) 30 September 1997 (30.9.97), see the entire document.	1-12

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

20 OCTOBER 1998

Date of mailing of the international search report

05 NOV 1998

 Name and mailing address of the ISA/US  
 Commissioner of Patents and Trademarks  
 Box PCT  
 Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

KHIEM NGUYEN

Telephone No. (703) 308-1738

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**